


Product data sheet

6102/111-0110-170-0111-11-A850-00
273105
STAHL



Compact light fitting emergency luminaire Explosion-protected Type: 6102/111-0110-170-0111-11-A850-00 Enclosure material: Thermoset
Dimensions (L x W x H): 44 cm x 185 mm x 105 mm Operating voltage AC: 100...240 V $\pm$ 10% Operating voltage DC: 100...250 V $\pm$ 10%
Application range (zones): 1 , 2 , 21 , 22 Gas explosion protection: II 2 G Ex db eb ib op is IIC Min. ambient temperature: -40°C Max. ambient
temperature: +50°C IP degree of prot. (IEC 60598): IP66 / IP67 Through wiring: Loop in/loop out wiring Installed terminal strip: PE + N + L1 + L2
+ L3 + D1+D2 Max. solid connect. terminals: 6 mm² Max. fine. strand. conn. term.: 4 mm² Drilled holes: 3 x M25 Accessories: Provided Screw
connections: 2 x M25 $\varnothing$ 7 – 17 mm Stopping plug: 2 x M25 x 1.5 Stopping plug material: Polyamide, black For further information, see: r-
stahl.com WebCode 6102A

Light output 1



1 x LED			
Nominal lamp power	9.7 W	LOR	100%
Lamp flux	490 lm	Total flux	490 lm
Luminous efficacy	51 lm/W	Total power	9.7 W
CCT	5000 K		
CRI	81		

Mounting mode

Wall mounted

Shape and measurements

Length: 58.15 in

Width: 3.35 in

Height: 3.39 in

Adjustability

Fixed

Electric

System power: 9.7 W

Ballast: ECG

Appliance Class: I

Protection

IP: 66

IK: 08

Other operating numbers

Ambient temperature range: -4...113°F