



Product data sheet

DAMP PROOF COMPACT GEN 1 1200 23 W 4000K IP66 GR
4058075210028
LEDVANCE



Damp-proof luminaire, through-wired (L, N, E). Product features: High luminous efficacy: up to 120 lm/W. Type of protection: IP66. Beam angle: 120°. Through-wiring 3x1.5mm² already installed. Polycarbonate housing. Product benefits: Uniform light distribution. Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps). Easy installation as mounting brackets can be positioned freely on the luminaire. Easy access to electrical terminal thanks to end caps with twist and lock mechanism. Tool-free electrical connection due to push button connector. 5 years guarantee. Areas of application: Industrial and storage facilities. Car parks and underpasses. Garages. Workshops, assembly lines. Equipment / Accessories: Stainless steel clamps with safety screws included. Mounting accessories included (suspension kit, theft protection kit). Safety advice: All electrical connections must be made by a qualified person.. Caution, risk of electric shock..

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	2800 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	8%
		Total power	23 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 50.79 in
Width: 3.39 in
Height: 2.68 in
Weight: 1.12 kg

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Anthracite / graphite

Electric

System power: 23 W
Appliance Class: II

Protection

IP: 66
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -31...122°F