


Product data sheet

SPINNER X FORUM
1886.ES50/..
PSM LIGHTING




built-up ceiling light - directional - down


Light output 1




1 x LED			
Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	455 lm	LOR	100%
Luminous efficacy	61 lm/W	ULOR	3%
CCT	4000 K	Total flux	455 lm
CRI	84	Total power	8 W



1 x LED			
Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	430 lm	LOR	100%
Luminous efficacy	57 lm/W	ULOR	3%
CCT	4000 K	Total flux	430 lm
CRI	84	Total power	8 W



1 x LED			
Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	435 lm	LOR	100%
Luminous efficacy	58 lm/W	ULOR	3%
CCT	3000 K	Total flux	435 lm
CRI	83	Total power	8 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7.5 W
410 lm
55 lm/W
3000 K
83

Socket
LOR
ULOR
Total flux
Total power

Gu10
100%
3%
410 lm
8 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7.5 W
410 lm
55 lm/W
2700 K
83

Socket
LOR
ULOR
Total flux
Total power

Gu10
100%
3%
410 lm
8 W



1 x LED


Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7.5 W
390 lm
52 lm/W
2700 K
83

Socket
LOR
ULOR
Total flux
Total power

Gu10
100%
3%
390 lm
8 W

Light output 2




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7.5 W
455 lm
61 lm/W
4000 K
84

Socket
LOR
ULOR
Total flux
Total power

Gu10
100%
3%
455 lm
8 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7.5 W
430 lm
57 lm/W
4000 K
84


Socket
LOR
ULOR
Total flux
Total power

Gu10
100%
3%
430 lm
8 W




1 x LED

Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	435 lm	LOR	100%
Luminous efficacy	58 lm/W	ULOR	3%
CCT	3000 K	Total flux	435 lm
CRI	83	Total power	8 W




1 x LED

Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	410 lm	LOR	100%
Luminous efficacy	55 lm/W	ULOR	3%
CCT	3000 K	Total flux	410 lm
CRI	83	Total power	8 W



1 x LED

Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	410 lm	LOR	100%
Luminous efficacy	55 lm/W	ULOR	3%
CCT	2700 K	Total flux	410 lm
CRI	83	Total power	8 W



1 x LED

Nominal lamp power	7.5 W	Socket	Gu10
Lamp flux	390 lm	LOR	100%
Luminous efficacy	52 lm/W	ULOR	3%
CCT	2700 K	Total flux	390 lm
CRI	83	Total power	8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.94 in

Width: 7.17 in

Height: 5.12 in

Adjustability

Rotatable

Electric

System power: 16 W

Appliance Class: I

Protection

IP: 20

IK: 02