


Product data sheet

RUBIN CLEAN LED 10400 MICRO-PRM SH E IP65 34 840 / 1220X620MM


19.4066.4221.34

LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 1220 x 620 x 78 mm. Diffuser: Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass). The efficiency of the optical system is 71,99%. Beam angle: (C0-C180) / (C90-C270) - 88° / 91,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 7536 lm. Power of luminaire: 56,3 W. Luminaire's light efficiency: 133,9 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 16 (B10), 26 (B16), 23 (C10), 37 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



8 x LED			
Nominal lamp power	7.038 W	LOR	83%
Lamp flux	1308 lm	Total flux	8734 lm
Luminous efficacy	186 lm/W	Total power	56.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.03 in

Width: 24.41 in

Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 56.3 W

Appliance Class: I

Protection

IP: 65

IK: 08

Other operating numbers

Ambient temperature range: 41...86°F