



Product data sheet

LD154DO 19.6W 500MA OB
LD154DO-P1-500-OB
LIGHTGRAPHIX



LD154DO Ø100mm Recessed Uplight. Constant Current. 19.6W 500mA 19° x 60° Oval beam. The LD154 is our most powerful fitting to date, delivering up to 1443lm from a minimal body depth of 71mm. It forms a new range of high-power uplight solutions for drive over (LD154DO), low glare (LD154DR) and asymmetric installations (LD154T). There are 3 LED engine options available. Our new P1 engine delivers the highest output, whilst the E3 offers an exceptional extra narrow beam of 9° and the N1, a 13° beam. The lens assembly features large 50mm optics which offer ultra-high efficiency, superior beam quality and low glare. Reaching heights of up to 14 metres, the LD154 demonstrates excellent size to output ratio and has been designed with a repairable engine, providing a robust circular solution for high-power uplight applications.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19.6 W	CRI	90
Total flux	1443 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	100%
		Total power	19.6 W

Mounting mode

Floor recessed

Shape and measurements

Height: 2.91 in
Diameter: 3.94 in

Adjustability

Fixed

Design

Material impression: Glass, Gloss, Matt, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 19.6 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
IK: 09
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...113°F