


Product data sheet

HALOSCAN ST HP 92735
23114 9230
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named HALOSCAN ST HP 92735, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 70 mm is needed and a min. depth for recessing of 55 mm. This luminaire is equipped with LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm with an optional driver, suitable for currents of 350mA. Light distributor: lens 35°.


Light output 1




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 0.04 in
Diameter: 3.07 in

Electric

System power: 12 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE