


Product data sheet


FLEXBAR SURFACE / SUSPENDED - 8W (6W/M) - SECONDARY CORNER - LEFT - DOWNLIGHT - WHITE REF - 4000K
FR08CSLXW
THORLUX LIGHTING



IP
20


Flexbar is an elegant surface mounted or suspended linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail

Light output 1



1 x LED			
Nominal lamp power	4 W	LOR	100%
Lamp flux	730 lm	Total flux	730 lm
Luminous efficacy	146 lm/W	Total power	5 W
CCT	4000 K		
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	4 W	LOR	100%
Lamp flux	730 lm	Total flux	730 lm
Luminous efficacy	146 lm/W	Total power	5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Electric

System power: 10 W

Shape and measurements

Length: 34.25 in

Width: 1.73 in

Height: 2.40 in

Protection

IP: 20

Adjustability

Fixed, Height adjustable