


Product data sheet


ALEA SPOT
641318.002.1
RZB



IP
20

Series: Alea Spot Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Pole: aluminium. Cover: plastic sphere, opal, satin finish. "Triple lamp; mains connection through pole to terminal in" "pole top; base plate: D 300. 4 mounting holes: D 10; pitch" circle for holes: D 230. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 586, B 75, H 2 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 1950lm System power: 15W Beam Angle: 60°/58° Number of fittings B10A: 38 Number of fittings B16A: 60 Inrush current: 8A Unified Glare Ratio: 16,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	1950 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	15 W

Mounting mode

Wall recessed

Shape and measurements

Length: 2.95 in
Width: 23.07 in
Height: 1.46 in

Adjustability

Fixed

Electric

System power: 15 W

Protection

IP: 20