



Product data sheet

PRIMA 1.5FT E-CON PCC 8000/840 2X5P
107736
TREVOS



resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces; variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting; optimal mounting height: 3 to 8 m; ON/OFF electronic driver (AC, DC on demand); Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: stainless steel + polyamide; Sealing: polyurethane (PUR), foam-filled base groove; Connection: external, 5-pole, 1.5 mm2 conductor cross-section (2.5 mm2 available on demand); Power: 47,4 W; Luminaire flux: 7460 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: - 25|45 °C; Weight: 2 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47.4 W	CRI	80
Total flux	8020 lm	LOR	100%
Luminous efficacy	169 lm/W	ULOR	4%
		Total power	47.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.28 in

Width: 3.86 in

Height: 3.31 in

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: Silver gray, White

Designer: TREVOS

Electric

System power: 47.4 W

Ballast: ECG

Appliance Class: I

Protection

IP: 66

IK: 10

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F