
Product data sheet

LUCAS VII (1-ARMED BEADED) 9.857.3066.16 LEIPZIGER LEUCHTEN



High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with fork-type painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole: dia. 76 mm, please order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



| | 1 x High pressure | mercury vapour lamp |
|--|-------------------|---------------------|
|--|-------------------|---------------------|

IP 55

| Nominal lamp power | 125 W | LOR | 80% |
|--------------------|---------|-------------|---------|
| Lamp flux | 6800 lm | ULOR | 4% |
| Luminous efficacy | 40 lm/W | Total flux | 5439 lm |
| ССТ | 3400 K | Total power | 137 W |
| CRI | 54 | | |
| | | | |



| 1 x High pressure mercury vapour lamp | |
|---------------------------------------|--|
|---------------------------------------|--|

| Nominal lamp power | 80 W | LOR | 80% |
|--------------------|---------|-------------|---------|
| Lamp flux | 4000 lm | ULOR | 4% |
| Luminous efficacy | 36 lm/W | Total flux | 3199 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

| Mounting mode | Electric |
|------------------------|------------------------|
| Pole top mounted | System power: 89-137 W |
| Shape and measurements | Protection |
| Height: 23.62 in | IP: 55 |
| Diameter: 22.44 in | |