


Product data sheet

SLOIN A SL IP54 LED1400-840 L1040 WW
42184582
ZUMTOBEL



LED light line IP54 with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 1390 lm, Luminaire efficacy: 75 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate including integrated reflector for asymmetric light distribution. Includes gear tray, reflectors, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP54. Dimensions: 1040 x 76 x 104 mm weight: 4.79 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18.5 W	CRI	80
Total flux	1390 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	18.5 W

Mounting mode

Pendant

Shape and measurements

Length: 40.94 in
Width: 2.99 in
Height: 4.09 in
Weight: 4.8 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 18.5 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 54
Designation labels: CE