



Product data sheet

ECLSOFTLINEARIP
ECLSOFTLINEARIP_FULL_FILTER INT
PROLIGHTS



The EclSoft Linear is an IP65 rated linear soft light, with all the main features of the successful EclPanel range, in a new form factor and waterproof design. Each of its 15 pixels can be controlled individually through DMX/RDM, Ethernet protocols, Wireless DMX (CRMX and W-DMX), or the built-in cinema effects engine. The EclSoft Linear has several colour control modes: RGBW, RGB, CMY, HSI, XY, RAW Direct, CCT linear and CCT presets with +/- green shift, source emulation and industry-standard colour gels. There are several accessories available for the EclSoft Linear, including optical filters and beam shaping accessories. The 230W RGB + Warm White LED engine producing nearly a 13,000 lumen output, whilst keeping perfectly mixed colours and precise white tones, from tungsten to daylight, maintaining a high CRI, TLCI and TM-30 values. The onboard driver, built-in power supply, easy rigging and cabling make this fixture the perfect tool for every film, TV or touring production Features: 230W RGB + Warm White engine, producing nearly a 13,000 lumen output CRI > 92 R9 > 96; TLCI > 87 15 individually controlled pixels with built-in cinema effects engine DMX/RDM control, Ethernet, and Wireless DMX (CRMX + W-DMX)

Light output 1



1 x LED			
Nominal lamp power	234.8 W	LOR	100%
Lamp flux	10487 lm	Total flux	10508 lm
Luminous efficacy	45 lm/W	Total power	250 W
CCT	0 K		
CRI	79		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 32.95 in
Width: 6.89 in
Height: 3.14 in

Adjustability

Rotatable, Tilttable, Free

Electric

System power: 250 W
Controller: DMX
Color adjustable
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 70°C
Designation labels: CE