

# Product data sheet

BTECL L30 LE3  
BTECL EMERGENCY  
DEXTRA




IP  
20




Btec Large Downlighter - Ø220mm, IP40 Recessed downlighter with spun aluminium housing, spring steel retaining clips and high transmission polycarbonate diffuser. Options: LE3 - Lithium Emergency (493 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest CB - Please specify 50v, 110v or 230v when ordering S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	493 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	3 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20.7 W	CRI	80
Total flux	2571 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	20.7 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.35 in  
Diameter: 8.66 in

## Adjustability

Fixed

## Electric

System power: 23.7 W  
Ballast: ECG

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Protection

IP: 20  
Designation labels: CE