

# Product data sheet

079-R135 LED 832  
GLAMOX




IP  
65

IK  
07

Light source R125: LED 70 832 R135: LED 70 832 R235: LED 180 830/840 Ballast Fixed output (HF). Body material & colour Luminaire housing in die-cast aluminium. Phosphor-chromated for extra protection and polyester powder coated paint finish. Black, white or silver grey. Front cover in frosted tempered glass. Silicone gasket. Screws made of stainless steel. Mounting Installation into supplied mounting box. Connection Cable inlet through membrane glands on backside of the luminaire. 3 pole 2,5 mm² screw terminal block. Outdoor use requires suitable flexible cables assuring the water tightness of the membrane gland.

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3200 K |
| Nominal lamp power | 4 W     | CRI         | 80     |
| Total flux         | 65 lm   | LOR         | 100%   |
| Luminous efficacy  | 16 lm/W | ULOR        | 8%     |
|                    |         | Total power | 4 W    |

## Mounting mode

Wall recessed

## Shape and measurements

Length: 5.24 in  
Width: 3.86 in  
Height: 9.25 in

## Adjustability

Fixed

## Electric

System power: 4 W

## Protection

IP: 65  
IK: 07