Product data sheet


DECORATIVE LIGHTING
V1-R0-90504-30000-2019030 COSMO 1200 MM SUSPENDED 190W 3000K
VARTON



IP 40 IK 03

• Round luminaire with homogenous illumination • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Suspended Input voltage (AC, 50Hz), V: 220...240 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: УХЛ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/interernoe-dekorativnoe-osveshchenie/cosmo/cosmo-1200-mm-podvesnye/svetodiodnyy-svetilnik-varton-cosmo-1200kh115-mm-190-vt-podvesnoy-cri90-3000-k-s-rasseivatelem-opal-_2/

Light output 1



1 x LED

Nominal lamp power	190 W	LOR	100%
Lamp flux	14600 lm	Total flux	14602 lm
Luminous efficacy	77 lm/W	Total power	190 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 4.53 in
Diameter: 47.24 in

Adjustability

Fixed

Electric

System power: 190 W

Protection

IP: 40
IK: 03