

Product data sheet


RWY 1500 L127 BD OP
RUNWAY (SURFACE/SUSPENDED)
DEXTRA



IP
20

Runway Surface/Suspended - 2000mm Surface/suspended linear luminaire, extruded aluminium trunking with painted finish and opal diffuser with uplight. Options: E3 - Emergency control gear ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence GY - Grey Finish WH - White Finish BL - Black Finish RWY SUSP 3M - Runway 3M single point suspension kit RWY SMK - Runway Surface Mount kit (single point) RWY INSTALL KIT - Runway Installation Kit (1 Kit per installation)

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	72.8 W	CRI	80
Total flux	8976 lm	LOR	100%
Luminous efficacy	123 lm/W	ULOR	4%
		Total power	72.8 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 58.23 in
Width: 2.56 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 72.8 W
Ballast: ECG

Protection

IP: 20