Product data sheet

FIT 20 48V SHORT DOUBLE FLOOD DIM DALI 3500K NTW
A3441233NTW-S
ARKOSLIGHT




ARKOSLIGHT

IP 20

Fit 48V is a spotlight for low voltage tracklight applications, available in different models (50, 35, 35 Double, 27, 27 Double, 20 and 20 Double). With its cylindrical geometry and essential forms, it stands out for its minimalistic design and functionality, as it can be oriented in any direction. The black perimeter around its mouth and its honeycomb accessory highlight its anti-glare vocation.


Light output 1



1 x LED

Nominal lamp power	2.1 W	LOR	87%
Lamp flux	150 lm	Total flux	131 lm
Luminous efficacy	71 lm/W	Total power	2.1 W
CCT	3500 K		
CRI	90		

Light output 2



1 x LED

Nominal lamp power	2.1 W	LOR	87%
Lamp flux	150 lm	Total flux	131 lm
Luminous efficacy	71 lm/W	Total power	2.1 W
CCT	3500 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 0.79 in
Width: 6.54 in
Height: 3.03 in

Adjustability

Rotatable, Tiltable

Electric

System power: 4.2 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20