



Product data sheet

6002/4128-0100-152-2220-22-8650
266724
STAHL



Linear luminaire With LED GRP Explosion-protected Type: 6002/4128-0100-152-2220-22 -8650 Spare of type: 6002/1182-5400-5232-6 6002/2182-5400-5232-6 6002/2182-5400-8232-6 Enclosure material: Polyester resin Translucent cover material: Polycarbonate Version: Standard Enclosure colour: Light grey (RAL 7035) Number of lamps: 1 Lamp wattage: 18 W Light distribution: 120°x120° with diffusing glass Luminous flux: 2.700 lm Luminaire efficacy: 150 lm/W Colour temperature: 6.500 K LED Service life: L90B50 ≥ 100.000 h Dimensions (L x W x H): 700 x 184 x 125 mm AC rated operational voltage: 110,00 - 240,00 V DC rated operational voltage: 110,00 - 250,00 V Application range (zones): 1 , 2 , 21 , 22 Gas explosion protection: II 2 G Ex db eb ib mb op is IIC T4 Gb Dust explosion protection: II 2 D Ex tb op is IIIC T100 °C Db Min. ambient temperature: -40 °C Max. ambient temperature: +50 °C Note: Through wiring: Max. 3x16 A Max. ambient temperature 2: +60 °C Note: Through wiring 2: Max. 3x10 A Impact strength (IK code): IK10 (IEC 62262) Diffuser: With diffuser Through wiring: With 5 conductors 2.5 mm² Ballast: 6045/211-120-10 Threaded plate: 2x SS430 stainless steel Drilled holes: 3 x M20 Without Screw connections: Can be ordered as accessories Stopping plug: Can be ordered as accessories Languages of the documentation: German English For further information, see: r-stahl.com WebCode 6002D

Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	2700 lm	ULOR	2%
Luminous efficacy	150 lm/W	Total flux	2700 lm
CCT	6500 K	Total power	18 W
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 27.48 in
Width: 6.61 in
Height: 5.07 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 18 W
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10
Explosion zone suitability: 1

Other operating numbers

Ambient temperature range: -40...140°F