


Product data sheet

LD1092 9.2W 700MA NB
LD1092-E3-700-NB
LIGHTGRAPHIX



LD1092 Ø75mm Recessed Downlight. IP40 / IP65. Constant Current. 9.2W 700mA 12° Narrow spot. The LD1092 is part of a range of ultra-shallow, high-power downlights designed for ceilings with a minimal recess depth. With two LED engines, this compact, high-quality downlight can deliver in excess of 900lm making it ideal for general downlighting, as well as wall washing and architectural applications. The adjustable lens assembly can be tilted up to 25° to allow ultimate flexibility when focusing the product. A matt black internal baffle helps to reduce glare and can be custom painted to suit the design scheme. Rated IP40 as standard, LD1092 can also be specified as IP65 for wet or humid areas including bathrooms and spas. With a minimalistic design it complements most interior project styles that require a high-power and adjustable light output, from a very compact, shallow fitting.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	85
Total flux	703 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	100%
		Total power	10 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.40 in
Diameter: 2.95 in

Adjustability

Tiltable

Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 10 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 40
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F