Product data sheet

EDLR 150/1100-840 W + DR150-MPS-G-D-W 0321305 + 0204883

RIDI








Recessed downlighter with LED Design: Recessed downlighter, diameter 150 mm with LED module, comprising reflector housing and gear tray. Fitted with RIDI LED module. Protection rating on the room side IP 40, ceiling side IP20. Reflector housing: Rigid mounting ring in die-cast metal with toolless fixing clips mechanism for ceiling mounting and reflector holding clips. Integrated fixture for toolless mounting of the decor ring and accessories. Decorative ring made of white polycarbonate with bayonet fitting. Functional module in white polycarbonate for mounting the reflector using the bayonet fitting. Diffusor made of transparent polycarbonate with internally satinised polycarbonate to protect the LED, clips into the functional module (opal diffuser available on request). Gear tray: Gear tray plate made of galvanised steel, accommodates the electrical components, mains connector block, cable strain relief and connecting cable to the LED module. Clip-on heat resistant polycarbonate cover. Gear tray 90 mm high in emergency lighting version. Electronic converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block 3x2.5mm². Suitable for direct voltage operation and use in central battery systems. Mounting: In addition to the standard fixing clips for clamping thicknesses from 0 to 25 mm, special accessory fixing kits such as panel mounting kits, reinforcement plates, cast concrete housings, plaster rings, inclined mounting kits or semi-recessed mounting kits can be ordered. EDLR 150/... W Diameter 150 mm. High-reflectance white reflector made of pure high-reflectance aluminium, powder coated similar to RAL9016. DR150-MPS-G-D-W Decor. float glass disc, microprisms with decor ring white

Light output 1



1 x LED	
Nominal lamp power	8 W
Lamp flux	1180 lm
Luminous efficacy	147 lm/W
CCT	4000 k
CRI	80

LOR	100%
Total flux	1180 lm
Total power	8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.91 in Width: 5.91 in Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 8 W

Protection

IP: 20