Product data sheet


KOMBIC 150 SF 2800 IP43 840 WFL DA BK/WH
K21SF3040WF840DBW
LAMP



IP 40

Suspended or ceiling mounting downlight model KOMBIC 150 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: >100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	13.5 W	LOR	100%
Lamp flux	1780 lm	Total flux	1778 lm
Luminous efficacy	132 lm/W	Total power	13.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.09 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 13.5 W
Appliance Class: I

Protection

IP: 40