
Product data sheet


SINUS CURVED SEGMENT DI/ID BLACK SAT. 45° R1440
P33-H54-9005E2830L3S
PLANLICHT



IP 40


low output LED 3000K CRI 90 29,5W 3400lm DALI https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.38 W	CRI	90
Total flux	850 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	7.38 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.38 W	CRI	90
Total flux	850 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	7.38 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.38 W	CRI	90
Total flux	850 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	7.38 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.38 W	CRI	90
Total flux	850 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	7.38 W

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 41.06 in
Width: 18.98 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 29.5 W

Protection

IP: 40