

# Product data sheet

ANTON II FF LED

9.135.8318.416-3


LEIPZIGER LEUCHTEN



IP  
65

height of lamp: 4.50m / 6.00m light standards: for low, medium and high lighting requirements lamp: incl. 1, 2 or 3 FF II-X LED modules, easy to replace colour temperature: 4,000K neutral white or 3,000K warm white surge protection: up to 10kV (1 puls/8kV) LED gear: incl. 4DIM driver, up to 100,000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/ DC compatible for operation with central battery systems (60% of the max. declared output power in AC operation or deviating according to customer's request – please specify when ordering) LED life expectancy: up to 100,000 hours, 50,000 hours/ L100/ B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical wide beam luminaire head: made of die cast aluminium, powder coated bracket: made of hot dip galvanised steel, powder coated column: incl. straight conical column with access door for cable junction box, made of hot dip galvanised steel, powder coated colour: RAL or DB glazing: polycarbonate, clear, impact resistant, UV-stabilised, to be hinged down wiring: via a plug and socket connector within the luminaire head installation: with root to be set into the ground accessory: cable junction box, cable, pole accessories, foundation – to be ordered separately application areas: parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distributor roads, main streets, paths, squares, car parks

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	52 W	CRI	70
Total flux	5870 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	5%
		Total power	52 W

## Mounting mode

Pole integrated

## Shape and measurements

Length: 27.95 in

Width: 11.81 in

Height: 7.32 in

Weight: 10.5 kg

## Adjustability

Height adjustable

## Electric

System power: 52 W

## Protection

IP: 65