Product data sheet

LERS6B/LESQS6B LED 6" SHALLOW ROUND AND SQUARE CYLINDERS
LE_6B40D010 EC6B30509730 6LBMMW1
COOPER LIGHTING



IP 47

Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Shallow extruded aluminum housing; Diecast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-4,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	41.8 W	CRI	97
Total flux	3126 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	41.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in
Diameter: 5.50 in

Adjustability

Fixed

Electric

System power: 41.8 W

Protection

IP: 47