
Product data sheet


LINE50HEX
LH50H-208301-HXXXO
EGLO



IP 20


surface mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22.92 W	CRI	80
Total flux	2659 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	22.92 W

Mounting mode

Pendant

Shape and measurements

Length: 79.84 in

Width: 69.13 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 137.55 W

Protection

IP: 20

Designation labels: CE