

# Product data sheet

X-LINE SLIGHT L-DOWN LED 1300 MICRO-PRM EDD 04 840 / L-572MM S-1,5M


19.4085.5123.04

LUXIONA



Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: 572 x 34 x 68 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 81,50%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 111°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 1229,7 lm. Power of luminaire: 8,6 W. Luminaire's light efficiency: 143 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 20 (B10), 31 (B16), 33 (C10), 53 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. There is the possibility of fitting a luminaire with a sound-absorbing housing.

## Light output 1



### 1 x LED

Nominal lamp power	8.6 W	LOR	83%
Lamp flux	1509 lm	Total flux	1259 lm
Luminous efficacy	175 lm/W	Total power	8.6 W
CCT	4000 K		
CRI	80		

## Mounting mode

Pendant

## Shape and measurements

Length: 22.52 in

Width: 1.34 in

Height: 2.68 in

## Adjustability

Fixed

## Design

Color of housing: Black

## Electric

System power: 8.6 W

Controller: DALI

Appliance Class: I

## Protection

IP: 40

IK: 04

## Other operating numbers

Ambient temperature range: 41...95°F