Product data sheet


ANNET 1 UNDERWATER PROJECTORS, FLOODLIGHTS
AE-50177-W-W40
LIGMAN



IP 68 IK 07

· Lamp LED · CRI Ra > 80 · MacAdam Ellipse 3 SDCM Life time L90B10 Ta 25° C 135,000, 300,000 Life time L80B10 Ta 50° C 310,000, > 500,000 · Colour 3000K and 4000K - Stainless steel body and fasteners in grade 316 - Single cable entry - One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable - Durable silicone rubber gasket - Clear toughened glass - Maximum depth 2 meters - Luminaire must be submerged when operational - Remote driver is included - Remote IP box is not included

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	8.3 W	CRI	80
Total flux	541 lm	LOR	100%
Luminous efficacy	65 lm/W	ULOR	100%
		Total power	8.3 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 6.30 in
Diameter: 4.21 in
Weight: 1.1 kg

Adjustability

Rotatable

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 8.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 68
IK: 07
Surface temperature: 40°C