Product data sheet

FREESTANDING LUMINAIRE LIGHTPAD OFFICE FOR SINGLE PERSON WO 2007.8027 - LGTPD4 L1L LED7200-930 WH 0IF SEDI CH

REGENT








Freestanding luminaire Lightpad Office for single person workstation, left, with LED, system power: 55 W, standby power 0.5 W, luminous flux of luminaire 7200 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax \ge 65° \le 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, without control element, in aluminium, white, RAL 9016, 1 integral control gear, SensoDim®, with light/movement sensor, 3m power supply cable with plug, base plate, full mould, oblong, ENEC certified, protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1258590 L = 782 mm, B = 275 mm, H = 19 mm, total height = 2000 mm

Light output 1



1	Y	П	FI	ח

Nominal lamp power	67 W	LOR	100%
Lamp flux	7200 lm	ULOR	73%
Luminous efficacy	107 lm/W	Total flux	7184 lm
CCT	3000 K	Total power	55 W
CBI	an		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 30.79 in Width: 11.97 in Height: 78.82 in Weight: 20.51 kg

Adjustability

Free

Design

Color of housing: White

Electric

System power: 55 W Appliance Class: I

Protection

IP: 20