

# Product data sheet

NADJA II (WALL FITTING)  
9.845.3162.05  
LEIPZIGER LEUCHTEN



IP  
55


Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 125 W   | LOR         | 77%     |
| Lamp flux          | 6800 lm | Total flux  | 5247 lm |
| Luminous efficacy  | 38 lm/W | Total power | 137 W   |
| CCT                | 3400 K  |             |         |
| CRI                | 54      |             |         |



### 1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W    | LOR         | 77%     |
| Lamp flux          | 4000 lm | Total flux  | 3087 lm |
| Luminous efficacy  | 35 lm/W | Total power | 89 W    |
| CCT                | 3400 K  |             |         |
| CRI                | 54      |             |         |

## Mounting mode

Wall mounted

## Shape and measurements

Height: 20.08 in  
Diameter: 20.08 in

## Electric

System power: 89-137 W

## Protection

IP: 55