Product data sheet


ECLDISPLAY_WHITE
ECLDISPLAYUNFC_FULL_PROFILE2040_MAX ZOOM
PROLIGHTS



IP 20 IK 08

EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay UNFC can be set and addressed through RDM, and includes a broad set of on-board input control options: DMX, DALI Type 8, phase-cut dimming or local knob dimming control The EclDisplay UNFC includes a high-efficiency 40W RGB + Warm White LED capable of delivering both a Full Colour spectrum and also tuneable White, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture. Features: Universal control through RDM, DMX, DALI Type 8, phase-cut dimming and local knob dimming 40W RGB + Warm White LED capable to deliver both a Full Colour generation and also Tunable White Multiple lens options: zoomable profile or wash optics

Light output 1



1 x LED

Nominal lamp power	34.6 W	LOR	100%
Lamp flux	344 lm	Total flux	345 lm
Luminous efficacy	10 lm/W	Total power	34.6 W
CCT	0 K		
CRI	98		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 34.6 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE