
Product data sheet


BERYL PROOF WALL K LED UP OR DOWN 2000 WIDE E IP65 04 840
19.3140.0028.04
LUXIONA



IP 65 IK 06

Outdoor luminaire. Assembly: mounted on wall. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: 210 x 120 x 370 mm. Weight 2,42 kg. Diffuser: transparent polycarbonate. The efficiency of the optical system is 87,27%. Beam angle: (C0-C180) / (C90-C270) - 93,8° / 89,6°. Light source type: LED. Colour of the light 4000 K. SDCM=2. CRI85. Lifetime of LED sources: 95000 (1) / 100000 (2) / 100000 (3) h L90/B10 (1) / L80/B10 (2) / L70/B10 (3). Luminaire luminous flux: 1979 lm. Power of luminaire: 12,5 W. Luminaire's light efficiency: 158,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 40 (B10), 60 (B16), 64 (C10), 102 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP65. Impact resistant: IK06. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG1. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED

Nominal lamp power	12.5 W	LOR	52%
Lamp flux	2268 lm	Total flux	1189 lm
Luminous efficacy	181 lm/W	Total power	12.5 W
CCT	4000 K		
CRI	85		

Mounting mode

Wall mounted

Shape and measurements

Length: 8.27 in
Width: 4.72 in
Height: 14.57 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 12.5 W
Appliance Class: I

Protection

IP: 65
IK: 06

Other operating numbers

Ambient temperature range: -13...86°F