Product data sheet

MIRAGE 3 IP65 VITALITY MEDIUM SEMI-SPEC

WHITECROFT









See lamps to select output and colur variants MIRAGE 3 recessed downlighter semi specular reflector, wide distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-50mm. Supplied with connected remote driver. Large round, 165mm diameter cut out, 173mm over bezel. IP65 rated from below. Emergency Output:- 8w - 40% 16.6w - 20% 26.5w - 12% 35w - 9%


Light output 1



1 x LED		
Nominal lamp power	26 W	LOR
Lamp flux	2786 lm	Total flux
Luminous efficacy	105 lm/W	Total power
CCT	4000 K	
CRI	80	



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1849 lm	Total flux	1849 lm
Luminous efficacy	111 lm/W	Total power	16.6 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	8 W	LOR	100%
Lamp flux	926 lm	Total flux	926 lm
Luminous efficacy	110 lm/W	Total power	8.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Electric

System power: 8.4-26.5 W

100% 2786 lm

26.5 W

Shape and measurements

Height: 3.94 in Diameter: 6.69 in

Adjustability

Fixed

Protection

IP: 65 IK: 10