Product data sheet

P-INF Q100WW LED1000-930 LDO AL TL
60818014
ZUMTOBEL



LED ceiling-recessed luminaire without cover frame, "trimless" (wallwasher), "Stable White"; asymmetric light distribution with maximum luminaire efficiency and optimum photometric properties; lamp(s): LED1000-930; Colour rendering Ra > 90, colour temperature 3000 K (warm white); Chromaticity tolerance (initial MacAdam): 2; total power: 9 W; Luminaire luminous flux: 925 lm, Luminaire efficacy: 103 lm/W; service life: 50000h at 95% luminous flux; includes controllable ballast, dimmable Dali only; modular, high quality optical unit consisting of reflector and LED light chamber integrated in optimised thermal management of die-cast aluminium; asymmetric smooth reflector in highly reflective aluminized finish, iridescence-free with additional oval-outline lens; reflector made of high-quality, UV-resistant polycarbonate; luminaire unit can be fitted quickly without tools using EASY-CLICK catch; IP44_IP20; luminaire wired with halogen-free leads; power connection: 5-pole terminal, loop-in/loop-out possible; mains voltage: 220-240V/ 0/50/60Hz; installation: tool-free quick installation using spring clips in ceilings of thickness 1-25mm; ceiling cutout: 100x100 mm, recessed depth: 130mm; weight: 0.62 kg; Note: Please order seating surround (planar surround) separately for installing the luminaire flush with the ceiling (see Accessories)

Light output 1



1 x LED

Nominal lamp power	9 W	LOR	69%
Lamp flux	1350 lm	Total flux	925 lm
Luminous efficacy	103 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.61 in
Width: 4.61 in
Height: 4.02 in
Weight: 0.6 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 9 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: II

Protection

IP: 20
Designation labels: CE, ENEC