Product data sheet

LOTIS SQUARE MR16 GE WHITE STRUCTURE 12611009

MODULAR









Square recessed spotlight Square recessed spotlights are becoming increasingly popular. Lotis Square is a compact, square version of our successful round Lotis series. The bulb sits deep down in a conical cup, which means it is less visible. Besides the regular version, there is also an IP version for use in damp rooms or outdoor environments. Available with a white or black structure.

Light output 1




1	Χ	LED

Nominal lamp power	6.5 W	Socket	Gu5.3
Lamp flux	380 lm	LOR	96%
Luminous efficacy	45 lm/W	Total flux	363 lm
CCT	2700 K	Total power	8 W
CRI	80		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	81%
Lamp flux	830 lm	Total flux	671 lm
Luminous efficacy	13 lm/W	Total power	52 W
CCT	2800 K		
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	85%
Lamp flux	830 lm	Total flux	703 lm
Luminous efficacy	14 lm/W	Total power	52 W
CCT	2800 K		
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	85%
Lamp flux	625 lm	Total flux	529 lm
Luminous efficacy	10 lm/W	Total power	52 W
CCT	2800 K		
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	87%
Lamp flux	830 lm	Total flux	722 lm
Luminous efficacy	14 lm/W	Total power	52 W
CCT	2800 K		
CRI	100		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.43 in Width: 3.43 in Height: 0.39 in

Adjustability

Fixed

Electric

System power: 8-52 W Appliance Class: III

Protection

IP: 20 IK: 01