# Product data sheet

CALEO LINEAR SUSPENDED - G3
AG3ASE-830H-L1182-Y
LIGHTNET



LED pendant luminaire. Direct only or direct-indirect light distribution. Luminaire body made of aluminum profile. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable cord suspension with transparent power supply cable.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 43 W | CRI | 82 |
| Total flux | 2852 lm | LOR | 100% |
| Luminous efficacy | 66 lm/W | Total power | 43 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 46.54 in
Width: 2.24 in
Height: 3.35 in

### Adjustability

Height adjustable

### Electric

System power: 43 W

### Protection