

# Product data sheet

STYLE II 51011 LED CG-S (WITHOUT PICTOGRAM FOIL ATTACHED)


40071356813

EATON EMERGENCY LIGHTING



- Compact exit sign or safety luminaire from high quality, UV-resistant, halogen-free plastic with LED-technology
- Modular constructed luminaire series permits combination with various fixing modules
- Includes transparent cap with simple snap mounting and pictogram foil set
- Exit signs with high luminance of > 500 cd/m<sup>2</sup> (white area) and good uniformity, in accordance with standards
- Minimum service requirement due to high service life of the LEDs (up to 50,000 hours)
- Simple mounting via quick mounting set (can be pre-assembled) with plug-in connectors for through-wiring
- Optionally available IP54 set (for electronic and light source) for increased sealing requirements both indoor and in protected outdoor areas
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditures by STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5.8 W	CRI	70
Total flux	98 lm	LOR	100%
Luminous efficacy	17 lm/W	Total power	5.8 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 13.46 in

Width: 3.74 in

Height: 2.36 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 5.8 W

Suitable for feed-through wiring

Appliance Class: II

## Information regarding emergency functions

Emergency lighting only

Emergency power supply: Central battery feed-in

Emergency sign: N/A

## Protection

IP: 41

IK: 03