



Product data sheet

RECESSED CEILING LUMINAIRE PURELITE D 22W CRI > 80 4000K DA
1022.3713 - PURLTD CR1226X110 LED3000-840 DALI
REGENT



Recessed ceiling luminaire Purelite D with LED, system power: 22 W, standby power 0.5 W, luminous flux of luminaire 3000 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, with ceiling trim, diffuser in synthetic material opal, 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0287), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, this product contains a light source of energy efficiency class A and EPREL registration number: 1124085 L = 1226 mm, B = 110 mm, EL = 1214 mm, EB = 96 mm, ET = 35 mm

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3000 lm
Luminous efficacy	100 lm/W	Total power	22 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.80 in

Width: 3.78 in

Height: 1.38 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 22 W

Appliance Class: I

Protection

IP: 20

IK: 08