Product data sheet


STREETPARK SMALL V2 LED PREMIUM 7700 ROAD E IP66 43 740
19.4402.1781.43
LUXIONA



IP 66 IK 09

Outdoor luminaire. Assembly: mounted on poles. The body material is aluminum. Colour - RAL 7035 (light grey). Dimensions: 610 x 205 x 85 mm. Diffuser: PMMA lenses and hardened transparent glass. The efficiency of the optical system is 87,80%. Beam angle: street light distribution. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>70. Lifetime of LED sources: 108000 h L95/B10. Luminaire luminous flux: 7057,2 lm. Power of luminaire: 45,3 W. Luminaire's light efficiency: 155,8 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 8 (B10), 13 (B16), 13 (C10), 22 (C16). Operating temperature range: -40 ÷ 50° C. Protection degree: IP66. Impact resistant: IK09. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The diameter of the mounting bracket is 60 mm.

Light output 1



1 x LED

Nominal lamp power	45.3 W	LOR	52%
Lamp flux	8038 lm	Total flux	4215 lm
Luminous efficacy	177 lm/W	Total power	45.3 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.02 in
Width: 8.07 in
Height: 3.35 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 45.3 W
Appliance Class: I

Protection

IP: 66
IK: 09

Other operating numbers

Ambient temperature range: -40...122°F