


Product data sheet

REK 533MM 180° EMISSION
55-E026-E3-CM
LEDSC4



LedsC4 Rek 533mm 180° Emission 55-E026-E3-CM Bollard for outdoor use. Structure material: Aluminium. Structure finish: Fir green. Diffuser material: Polycarbonate. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 3.39 Product width or diameter (mm): 150 Product height (mm): 534 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: NICHIA. Driver brand: TCL. Maximum power of light source: 11.4W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. % de Flickering: <6%. Real flux (lm): 325. Real lm/W: 24. Voltage / frequency range: 220-240V/50-60Hz. Voltage: 11.9. Equipment included: Yes. Total power: 13.7. Power factor: 0.95. Dimmable equipment included: DALI-2.

Light output 1



1 x LED			
Nominal lamp power	13.7 W	LOR	100%
Lamp flux	325 lm	Total flux	325 lm
Luminous efficacy	24 lm/W	Total power	13.7 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 20.94 in

Adjustability

Fixed

Electric

System power: 13.7 W

Appliance Class: I

Protection

IP: 66

IK: 10