

Product data sheet

BARIS 40 LED N 3900LM PLX DALI I KL. IP20 1421MM 830 BIALY 46W
319716
LENA LIGHTING



319716 BARIS 40 LED N 3900lm PLX DALI I KL. IP20 1421mm 830 BIALY 46W Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	46 W	CRI	80
Total flux	3900 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	46 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 55.94 in
Width: 1.57 in
Height: 2.09 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 46 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F