Product data sheet


RUNDO24 290-280K-10GGM3/830, S
290-280K-10GGM3/830
HALLA



IP 20


290-280K-10GGM3/830, S Luminaire surface/wall mounted/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 804 x 804 x 24 mm Type of installation: Surface, Wall mounted, Suspended Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36.4 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	137 lm/W	Total power	36.4 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	260 lm	LOR	100%
Luminous efficacy	173 lm/W	Total power	1.5 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Height: 0.94 in
Diameter: 31.69 in

Adjustability

Fixed

Electric

System power: 37.9 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20