# Product data sheet


DEECOS S MINI
742197.003.3
RZB



IP 20 IK 06

Series: DEECOS S mini LED surface-mounted projector in modern design with no visible cooling ribs. Housing made of die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With multi adapter for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: deep black, matt (RAL 9005) Diameter: 87 mm Height: 214 mm Lamp: LED Socket: without socket Colour temperature: 3500K Colour rendering index (CRI): 92 System power: 20 W Rated luminous flux: 2650 lm Beam angle Down: 60° Luminous efficiency: 133 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 20 W | CRI | 90 |
| Total flux | 2650 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 13% |
| | | Total power | 20 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Height: 8.43 in
Diameter: 3.43 in

### Adjustability

Rotatable, Tiltable

### Design

Color of housing: Black

### Electric

System power: 20 W

### Protection

IP: 20
IK: 06