
# Product data sheet


GANDALF 26 FLOODLIGHTS,PROJECTORS
GA-51111-ME-W40
LIGMAN



IP 66 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Hot-dipped galvanised steel mounting bracket allows for ceiling, wall or surface mounting - Integral control gear

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 54.5 W | CRI | 80 |
| Total flux | 5317 lm | LOR | 100% |
| Luminous efficacy | 98 lm/W | ULOR | 100% |
| | | Total power | 54.5 W |

### Mounting mode

Standing / Bollard, Wall mounted

### Shape and measurements

Length: 18.31 in
Width: 12.60 in
Height: 4.72 in
Weight: 7 kg

### Adjustability

Free

### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 54.5 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

### Protection

IP: 66
IK: 08
Surface temperature: 40°C