Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-R3-00350-31PR0-4003530 GR350 2.0 1188X294X50 MM IP40 35W 3000K PRISM
VARTON



IP 40 IK 02

LED luminaire solution for GRILIATO ceilings. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Height/depth: 50 Length: 1 188 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK02 Width: 294 Power factor: 0,95 https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr350-2-0-1188kh294kh50-mm-ip40/svetodiodnyy-svetilnik-varton-gr350-2-0-35-vt-3000-k-1188kh294kh50-mm-s-plankami-dlya-podvesa-i-rass_3/

Light output 1



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	4515 lm	Total flux	4515 lm
Luminous efficacy	129 lm/W	Total power	35 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.77 in
Width: 11.57 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40
IK: 02