Product data sheet


VIALUME1.740.CLII.CLO.ÖVERGÅNGSSTÄLLE
304226
FAGERHULT



IP 66 IK 09

Montage Stolptoppsarmatur som i grundutförande kan monteras på Ø 48 mm stolparm. Tillbehör för övriga montagemöjligheter beställs separat, se Tillbehör. Steglös tiltfunktion ±15º för perfekt inställning. Stolphöjd 5-8 m. Anslutning Anslutningskabel 10 m 2G1,5mm² av typ H05RN-F. På förfrågan finns även DALI varianter som levereras med 4G1,5mm². Andra kabelvarianter på förfrågan. Utförande Armaturhus och stolpfäste av pressgjuten aluminium. Aluzink-behandlade rostfria skruvar. Driftdon är inbyggt i armaturen. Härdat planglas IK09. PMMA kupa med IK10 på förfrågan. Optik Linserna är speciellt utvecklade för övergångsställen vid högertrafik. Ljusstyrning CLO (Constant Light Output) innebär att armaturen ger samma ljusmängd under hela dess livslängd. DALI variant på förfrågan. Design ÅF Lighting och Tuxen Design. Standardfärg Alugrå (RAL 9006, glans 70). På förfrågan finns även antracitgrå (Gris 900 Sablé, strukturlack), svart (RAL 9005, strukturlack) och vit (RAL 9010, glans 50).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	44 W	CRI	70
Total flux	5506 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	44 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.27 in
Width: 17.32 in
Height: 8.28 in

Adjustability

Tiltable

Design

Color of housing: Black, Silver gray, White

Electric

System power: 44 W

Protection

IP: 66
IK: 09