


Product data sheet

MINI TUBE
7144-I-3-530-XX
UNILAMP



TUBE a family of cylindrical shaped wall light, ceiling light and Area light. It is available in 3 different sizes. They are protected from the ingress of dust and water and are used in both outdoor and indoor environments. Operating with high lumen output LED in 3 color temperature 2700K, 3000K and 4000K. TUBE can solve many lighting tasks in modern architectural surrounds and are widely used in illuminating columns and facades. The body components are made from extruded and LM6 die-cast aluminium which make them highly corrosion resistant to any extreme environment. The bollard and pole light version gives a great level of downward light in respect to the lighting pollution issue. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-2 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • High efficiency reflector. • Weather proof grommet. • GFR PA6.6 terminal block. • Installation work has to be carried on according to the enclosed installation manual.

Light output 1



1 x LED			
Nominal lamp power	14 W	LOR	88%
Lamp flux	1590 lm	Total flux	1396 lm
Luminous efficacy	114 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 8.50 in
Width: 4.13 in
Height: 43.31 in

Adjustability

Fixed

Electric

System power: 16 W
Appliance Class: I

Protection

IP: 65
IK: 07