


Product data sheet

VIGILANT LED HIGH BAY 27000 LUMENS, MEDIUM DISTRIBUTION, CLEAR GLASS LENS
HEX7MCPEXXXXXN
DIALIGHT



Vigilant LED High Bay 27,000 Lumens 206 Watts 480V AC Passive Cool White, 80CRI Clear Glass Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK05 Medium Distribution IP66 Scaled IED File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	206 W	CRI	80
Total flux	27002 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	206 W

Mounting mode

Pendant

Shape and measurements

Height: 3.00 in

Diameter: 15.96 in

Adjustability

Rotatable, Tilttable

Electric

System power: 206 W

Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC

Appliance Class: I

Protection

IP: 66

IK: 05