


Product data sheet

BEAMLINE SLIM
742172.004.1
RZB




IP
20

IK
06

Series: BEAMLINE SLIM Linear surface mounted projector for aesthetically sophisticated lighting. Housing: metal, powder-coated. Perfect heat management with an aluminium heat sink. Rotation range: 356°. Swivel range: 90°. LED light unit with MRS technology: Mini-Reflector-System made of metallised thermoplastic with prismatic black glare-suppressing frame for pleasant glare-free light (RUG < 10). Wide beam light distribution. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Converter integrated in the adapter. Colour: silver Length: 285 mm Width: 35 mm Height: 80 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 25 W Rated luminous flux: 2050 lm Beam angle Down: 47° Luminous efficiency: 82 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	90
Total flux	2050 lm	LOR	74%
Luminous efficacy	82 lm/W	ULOR	20%
		Total power	25 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.38 in
Width: 11.22 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 25 W

Protection

IP: 20
IK: 06