


Product data sheet

ECOLINE OFFICE 1200 33W LED 3000K RA>80 CD-DA DP-SM
8246089641
SG ARMATUREN



Box Lean is available with double parabolic louvre and is suitable for schools and office lighting. Low energy consumption. Cost-cutting solution by avoiding the hassle of relamping. Light Distribution Direct Light source LED (3000K/4000K): D: 19W, 33W, 39W D/I: 34W, 39W Ra>80 SDCM: 3 L80/B10 >50.000h at Ta=25°C. Optics Direct: PMMA and satin-matt double parabolic louvre. Materials and finish Housing: Powder coated steel white 25% gloss. Double parabolic louvre in Miro finish. LED cover in PMMA. Control Gear Electronic driver: CD. CD-DA (DALI). Protection Class I, IP20, Ta=25°C, CE. Mounting/Connection Wire suspended or surface mounted. Adjustable wire suspensions to be ordered separately (2x2m). Cable entry on top of luminaire or in end caps. Connection direct in terminal block.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	33 W	CRI	80
Total flux	3690 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	33 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.24 in

Width: 5.59 in

Height: 2.48 in

Adjustability

Fixed

Electric

System power: 33 W

Appliance Class: I

Protection

IP: 20