Product data sheet

PROFILE MINI AREA 20 UP | 80 DOWN
P11XDA30X04 - 18W 3000K 1.2M, 120-277V DRIVER
FLUXWERX ILLUMINATION



Profile Mini is a high performance indoor, linear suspended luminaire with a signature architectural form and luminous open interior, 2/3 of the scale of Profile. Its anidolic optical system supports a wide range of applications via 4 distributions from 100 Down to 65 Up | 35 Down, as well as independently controlled hemispheres. This also allows wider spacing – up to 3.5m on centre – and fewer luminaires. Available in discrete 1.2m (4ft), 1.8m (6ft) or 2.4m (8ft) lengths, as well as continuous rows, completed by a choice of 4 endcap styles – Bevel, Flat, Capsule or Square.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	80
Total flux	1998 lm	LOR	100%
Luminous efficacy	118 lm/W	ULOR	75%
		Total power	17 W

Mounting mode

Pendant

Shape and measurements

Length: 48.00 in
Width: 1.50 in
Height: 2.00 in

Adjustability

Height adjustable

Design

Color of housing: Black, White, Silver gray

Electric

System power: 17 W

Protection

IP: 20
Designation labels: CE, UL